

12LP-12

TANDEM AXLE LOW PROFILE DUMP

G.V.W.R.	12,000#	AXLES	Two 6000# Cambered Axles w/ Elec. Brakes
G.A.W.R. (EA. AXLE)	6,000#	SUSPENSION	Multi-Leaf Slipper Spring w/ Equalizer
COUPLER	Adjustable 2-5/16" Bulldog	TIRE	LT235/85-16 Load Range E
SAFETY CHAINS	1/4" Grd. 70 w/ Safety Latch Hook (2 ea.)	WHEEL	16 X 6 White Spoke 8 Bolt
JACK	7000# Top Wind (Bolted On)	FLOOR	12 Ga. Smooth Steel
TONGUE	6" Channel Fold Back	LIGHTS	D.O.T. Stop, Tail, Turn and Clearance
FRAME	6" Channel	ELEC. PLUG	6 Way
CROSSMEMBERS	4" - 13# I-Beam	FINISH (PREP)	Acid Etched w/White Phosphorus, Undercoated w/Panther 813 & Two Coats Primer
BED CROSSMEMBERS	2" X 2" Square Tubing	FINISH	Painted w/ 2 Coats High Solid <i>Supreme</i> Acrylic Automotive Grade Enamel, and Pinstriped
BED LONG SILS	4" Channel		
BED SIDE RAILS	3" X 6 1/2" Formed Angle		
FENDERS	14 Gauge Diamond Plate Double Broke Teardrop		

STANDARD FEATURES

- Complete Break-A-Way System w/ Charge Line
- Enclosed Pump & Battery Box Mounted In Front of Bed
- Self Contained Electric Hydraulic Scissor Lift
- 26" 12 Ga. Sides w/ Formed Channel Supports
- Protected Lighting
- 16 Stake Pockets (Sides & Front)
- 1 Piece 12 Ga. Floor
- Double Rear Gates w/ Cam Latch
- 45 Degree Dump Angle
- Lockable Control Unit
- 1/2" Tie Rail On All 4 Sides
- Removable Header Across Rear

12LP-12



TRAILER WEIGHTS & CAPACITIES

LENGTH	EMPTY WEIGHT	BOX CAPACITY
12'	3,450#	5.7 Yards

OPTIONS

HYD2	Hydraulic Brakes on 2 Axles, 2-5/16" Adjustable Demco Actuator
HDLJ	Heavy Duty 10K Top Wind DropLeg Jack
SP	16" Spare Tire & Wheel - Load Range E
SPMT	Spare Tire Mount (Side)
SR7	7' Slide In Ramps
AP	Adjustable Pintle In Channel

Effective January 1, 2003 (Specifications and Options subject to change without notice.)